

FKE-K2 series Kitchen Exhaust Purifier



Catering fume purifier

Two-stage plate spike ionization technology



Smart operation

PWM intelligent power supply, work/maintenance/ fault indicator light for users to understand the status, RS485 signal transmission, convenient background management.



Installation regardless of left or right

The direction of the entrance and exit can be adjusted according to the needs of the site, and the on-site construction and installation are convenient.



Humanized design

Modular combination, nested double-opening door, easy to maintain, anti-UV paint, electrostatic spraying process, to ensure the equipment anti-corrosion and anti-rust.



Product Parameter

	Model	FKE-06K2	FKE-08K2	FKE-12K2	FKE-15K2	FKE-20K2	FKE-23K2
Purification Efficiency	Processed Air Volume(m³/h)	6000	7500	12000	15000	20000	22500
≥92%	Pressure Drop(Pa)	≤95					
Purification Efficiency	Processed Air Volume(m³/h)	1000	1700	8000	9400	13000	14100
≥97%	Pressure Drop(Pa)	≤65					
Input Power(V/Hz)		220 240~50 60					
Rated Power (W)		120	125	240	250	360	375
Dimension(L *W*H mm)		625*806*705	625*900*705	625*1452*705	625*1640*705	625*2098*705	625*2380*705
Equipment Weight (kg)		65	72	109	123	153	174
Status Indication		Operating, Maintenance, Failure					
Options		Oil collecting tray, Air distribution plate					
Maintenance Space (mm)		1030					
Mounting Feet Height (mm)		130					

*Default airflow direction is left inlet and right outlet, and the direction can be reversible on site. The purification efficiency is based on infrared spectrophotometry.

Product Dimension

