

Product Parameter

Model	FKH11-16	FKH11-18	FKH11-20	FKH11-22	FKH11-24
Processed Air Volume(m ³ /h)	3200	3600	4000	4400	4800
Purification Efficiency	98%				
External Static Pressure (Pa)	200				
Sound Pressure Level dB (A)	80				
Input Power (V/Hz)	380/50				
Rated Power (W)	ESP	280	280	280	280
	Fan	1100	1100	1500	1500
Dimension (L*W*H:mm)	1600*1100*977	1800*1100*977	2000*1100*977	2200*1100*977	2400*1100*977
Equipment Weight (kg)	210	217	259	267	275
Function of Touch Screen	One - Touch Activation From a Distance, Power On/Off, Purification On/Off, Off Delay				
Maintenance Space (mm)	500				

Model	FKH13-16	FKH13-18	FKH13-20	FKH13-22	FKH13-24
Processed Air Volume(m ³ /h)	3200	3600	4000	4400	4800
Purification Efficiency	98%				
External Static Pressure (Pa)	200				
Sound Pressure Level dB (A)	80				
Input Power (V/Hz)	380/50				
Rated Power (W)	ESP	280	280	280	280
	Fan	1100	1100	1500	1500
Dimension (L*W*H:mm)	1600*1300*977	1800*1300*977	2000*1300*977	2200*1300*977	2400*1300*977
Equipment Weight (kg)	217	225	268	276	284
Function of Touch Screen	One - Touch Activation From a Distance, Power On/Off, Purification On/Off, Off Delay				
Maintenance Space (mm)	500				

